

**Filthy Motorsports Beadlock and Race Wheel Order Form**  
 p. 303-834-7895 | f. 720-746-6251 | e. ben@filthyms.com  
 www.FilthyMotorsports.com

Customer Name: \_\_\_\_\_ Order #: \_\_\_\_\_

Address: \_\_\_\_\_

Phone: \_\_\_\_\_ Email: \_\_\_\_\_

Wheel Brand & Model: \_\_\_\_\_ Quantity: \_\_\_\_\_

Wheel Size: \_\_\_\_\_ Vehicle: \_\_\_\_\_

Notes / Details / Special Instructions: \_\_\_\_\_

| Backspacing                    | Bolt Pattern                       | Center Bore                          | Stud Diameter                   | Lug Nut Taper                       |
|--------------------------------|------------------------------------|--------------------------------------|---------------------------------|-------------------------------------|
| <input type="checkbox"/> 2.75" | <input type="checkbox"/> 5 x 135mm | <input type="checkbox"/> 3.25"       | <input type="checkbox"/> 7/16"  | <input type="checkbox"/> 60° Acorn  |
| <input type="checkbox"/> 3.00" | <input type="checkbox"/> 5 x 150mm | <input type="checkbox"/> 3.30"       | <input type="checkbox"/> 1/2"   | <input type="checkbox"/> 90° Acorn  |
| <input type="checkbox"/> 3.25" | <input type="checkbox"/> 5 x 205mm | <input type="checkbox"/> 3.49"       | <input type="checkbox"/> 9/16"  | <input type="checkbox"/> Flange (*) |
| <input type="checkbox"/> 3.50" | <input type="checkbox"/> 5 x 4.5"  | <input type="checkbox"/> 4.25"       | <input type="checkbox"/> 5/8"   | <input type="checkbox"/> Ball       |
| <input type="checkbox"/> 3.75" | <input type="checkbox"/> 5 x 4.75" | <input type="checkbox"/> 4.75"       | <input type="checkbox"/> 11/16" | <input type="checkbox"/> _____      |
| <input type="checkbox"/> 4.00" | <input type="checkbox"/> 5 x 5"    | <input type="checkbox"/> 5.125"      | <input type="checkbox"/> 10mm   |                                     |
| <input type="checkbox"/> 4.25" | <input type="checkbox"/> 5 x 5.5"  | <input type="checkbox"/> 5.15"       | <input type="checkbox"/> 12mm   | <b>*Flange Dia.</b>                 |
| <input type="checkbox"/> 4.50" | <input type="checkbox"/> 6 x 135mm | <input type="checkbox"/> 6.330"      | <input type="checkbox"/> 14mm   | _____                               |
| <input type="checkbox"/> 4.75" | <input type="checkbox"/> 6 x 5.5"  | <input type="checkbox"/> _____       | <input type="checkbox"/> _____  |                                     |
| <input type="checkbox"/> 5.00" | <input type="checkbox"/> 6 x 6.5"  |                                      |                                 | <b>Lug Bore</b>                     |
| <input type="checkbox"/> 5.25" | <input type="checkbox"/> 8 x 170mm | <b>Wheel Fit</b>                     |                                 | <input type="checkbox"/> Standard   |
| <input type="checkbox"/> 5.50" | <input type="checkbox"/> 8 x 6.5"  | <input type="checkbox"/> Lug-Centric |                                 | <input type="checkbox"/> Oversize   |
| <input type="checkbox"/> _____ | <input type="checkbox"/> _____     | <input type="checkbox"/> Hub-Centric |                                 | <input type="checkbox"/> _____      |

\*Not all configurations are available on all wheel models.

- I understand that beadlock wheels are for race use only and not intended for street or highway use.
- I understand that beadlock wheels may lose air pressure faster than a typical street wheel.
- I understand that beadlock wheels require frequent checking and tightening of beadlock ring bolts.
- I understand that custom drilled beadlocks and race wheels are non-returnable and non-refundable.

Signature: \_\_\_\_\_ Date: \_\_\_\_\_

